

www.parkersteel.co.uk

DECLARATION OF PERFORMANCE

(according to regulation EU No 305/2011)
Hollow Section S235-JRH

Cold formed hollow sections produced from non-alloy steel Grade S235JRH / 1.0039 according EN 10219-1

Cold formed steel hollow sections for general use. Supplied with 2.2 certification to EN 10204

Head Office: ParkerSteel Limited Vauxhall Road, Canterbury Kent CT1 1HD

Tel: 01227 783333 Website: www.parkersteel.co.uk View DOP: www.parkersteel.co.uk/dop

UKCA Marking Notified Body (No. 2273)

Steel Construction Certification Scheme 4 Whitehall Court, Westminster London, SW1A 2ES

Tel: 020 7839 8566 Website: www.steelconstruction.org

System of assesment and verification of constancy of performance of the product:

System 2+

Steel Construction Certificate Scheme has performed (i) intial inspection of the manufacturing plant and factory product control and (ii) continuous surveillance, assessment and evaluation of factory production control and issued Factory Production Control certificate 2273-CPR-0025 and Welding Certificate 2273-CPR-0025-WC.

| Yield strength Tensile strength Elongation (longitudinal) | rectangul sect | ar hollow | In accord EN 1021 | ance with | |
|---|--|---|----------------------|--------------------------------------|--|
| Tensile strength Elongation (longitudinal) | | Round, square and rectangular hollow sections | | 9-2: 2006 | |
| Elongation (longitudinal) | Nominal thickness (mm) | | Values Min (MPa) | | |
| Elongation (longitudinal) | > | <= | | | |
| Elongation (longitudinal) | - | 16 | 235 | | |
| (longitudinal) | | minal thickness Values (mm) Min (MPa) | | | |
| (longitudinal) | /- | 16 | min | max | |
| (longitudinal) | | 10 | 360 | 510 | |
| Impact strength | Nominal thickness (mm) | | Values Min (%) | | |
| Impact strength | <=16 | | 22 | | |
| (longitudinal) | Grade | Nom. Thk.(mm) | | npact Value (J) at Test Temp (°C) | |
| | JRH | <=16 | 27J at + 20°C | | |
| Weldability CEV | Nominal thickness (mm) | | Values Max (%) | | |
| | <=16 | | 0.35 | | |
| Durability | Nominal thickness (mm) | | Values Max (%) | | |
| | | | C: | 0,18 | |
| | <=16 | | Mn: | , | |
| | | | P: | -, | |
| | | | S: | -, | |
| | | | N: | 0.012 | |
| | FF deoxidation* | | | | |
| | Durability is also dependent on any method of protection subsequently applied and the type and thickness of the coatings | | | | |
| Note: *FF - Fu | type a | and unicknes | ss of the coa | RUITIQS | |



Head Office: ParkerSteel Limited
Vauxhall Road
Canterbury
Kent
CT1 1HD

Hollow Section 235-JRH

EN 10219-1: 2006

Cold formed hollow sections produced from non-alloy steel
Grade S235JRH / 1.0039 according EN 10219-1

Cold formed steel hollow sections for general use. Supplied with 2.2 certification to EN 10204

Elongation:

Tensile Strength:

Yield Strength: EN10219-1

Impact Strength:

Weldability: Durability:

Dangerous Substances:

No Performance Determined

Lalit Premchandani

Managing Director

ParkerSteel Limited

Date: April 2025

